



(19) **United States**

(12) **Patent Application Publication**
TANDON

(10) **Pub. No.: US 2019/0126325 A1**

(43) **Pub. Date: May 2, 2019**

(54) **SYSTEM AND METHOD FOR SORTING OBJECTS**

(52) **U.S. Cl.**
CPC **B07C 5/362** (2013.01); **B07C 5/3408** (2013.01); **B07C 5/342** (2013.01)

(71) Applicant: **OPTISORT, LLC**, Horseheads, NY (US)

(57) **ABSTRACT**

(72) Inventor: **PARAG TANDON**, Dover, MA (US)


A system for sorting objects is provided. For instance, the system includes a first sensor, a sorting actuator, a second sensor and a controller. The first sensor observes the objects. The sorting actuator sorts the objects. The second sensor observes the sorted objects. The sorting actuator may be actuated by the controller using sorting rules, historical system data and observations of the objects. The sorting rules may be updated by the controller using observations of the sorted objects. In another aspect, a method is provided. The objects are observed. The objects are sorted using sorting rules, historical system data and observations of the objects. The sorted objects are observed. The sorting rules are updated using the observations of the sorted objects.

(21) Appl. No.: **15/797,613**

(22) Filed: **Oct. 30, 2017**

Publication Classification

(51) **Int. Cl.**
B07C 5/36 (2006.01)
B07C 5/342 (2006.01)
B07C 5/34 (2006.01)






FIG. 1




FIG. 2




FIG. 3




FIG. 4

SYSTEM AND METHOD FOR SORTING OBJECTS

BACKGROUND

[0001] The subject matter disclosed herein relates to the sorting of objects, such as glass objects, for example in recycling sorting applications. By way of example, after collection of recyclable glass, a need exists to sort the glass by color so that different colored glass may be effectively processed or sold for reuse. In such applications, even a small amount of foreign material can adversely impact an entire batch of glass of a single color. For example, ceramic pieces can contaminate a batch of glass, and during subsequent processing could explode and damage the batch. In addition, an unacceptable amount of colored glass could make clear flint glass unacceptable for reuse and/or reduce the value of the material, impacting its price in an open market.

[0002] Other applications for sorting of objects abound. Fruit, vegetables, manufactured items, mail, and other items are routinely encountered in a state where they are not separated by type. Yet separation is desired so that like objects may be transported or sold separately. Separated objects usually have higher value than the mixed objects.

[0003] Automated sorting machines have been contemplated in the industry, and typically operate by using a camera and a sorting actuator, under the guidance of a control system. The control system uses predetermined algorithms and rules to activate the sorting actuator to move passing objects into different bins for collection.

[0004] These sorting machines are very sensitive to changes in the flow rate of objects, variations in conveyor belts, deviations in the sizes, shapes or colors of objects, system wear and tear, and other parameters. In addition, the sorting machines are specially designed for one or just a few sorting applications, and are not readily deployed in different applications.

[0005] And the sorting systems are very expensive, require expensive conveyor belts, and cannot be readily moved about a facility, such as a recycling or sorting facility. Therefore, a need exists for sorting systems and methods that have improved performance, greater flexibility, and lower cost of ownership.

SUMMARY

[0006] A system for sorting objects is provided. For instance, the system includes a first sensor, a sorting actuator, a second sensor and a controller. The first sensor may be for observing the objects. The sorting actuator may be for sorting the objects. The second sensor may be for observing the sorted objects. The sorting actuator may be actuated by the controller using sorting rules, historical system data and observations of the objects. The sorting rules may be updated by the controller using the observations of the sorted objects.

[0007] In another aspect, a method is provided. Objects are observed. The objects are sorted using sorting rules, historical system data and observations of the objects. The objects are observed. The sorting rules are updated using observations of the sorted objects.

[0008] An advantage that may be realized in the practice of some disclosed embodiments of the system or method for sorting objects is that the problem of sorting objects when

conditions are variable (flow rate, position, etc.) is solved by observing the result of an sorting actions and updating the sorting methods based on the observation

[0009] The above embodiments are exemplary only. Other embodiments are within the scope of the disclosed subject matter.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] So that the manner in which the features of the invention can be understood, a detailed description of the invention may be had by reference to certain embodiments, some of which are illustrated in the accompanying drawings. It is to be noted, however, that the drawings illustrate only certain embodiments of this invention and are therefore not to be considered limiting of its scope, for the scope of the disclosed subject matter encompasses other embodiments as well. The drawings are not necessarily to scale, emphasis generally being placed upon illustrating the features of certain embodiments of the invention. In the drawings, like numerals are used to indicate like parts throughout the various views.

[0011] FIG. 1 depicts a system for sorting objects, in accordance with one or more aspects set forth herein;

[0012] FIG. 2 depicts a method for sorting objects, in accordance with one or more aspects;

[0013] FIG. 3 depicts further details of the system of FIG. 1, in accordance with one or more aspects set forth herein; and

[0014] FIG. 4 depicts an example of operation of the system of FIG. 1, in accordance with one or more aspects set forth herein.

DETAILED DESCRIPTION

[0015] Embodiments of the disclosed subject matter provide techniques for sorting objects, such as glass objects, e.g., in recycling applications. Other embodiments are within the scope of the disclosed subject matter.

[0016] The present disclosure relates, in part, to systems and methods for sorting objects, such as glass objects typically found in the recycling of glass bottles and articles. Advantageously, in one embodiment, the system includes two or more sensors, such as a cameras, that watch the objects as they pass through a sorting actuator. In one application, the glass objects are sorted for color by the actuator. Typically, the sorting actuator may use a puff of air or fluid, or may use a mechanical paddle, magnetic system, etc., to move the objects by different amounts so that the objects land in different bins as the pass through the system. In other applications, different input material may be sorted, and as the systems have a lower cost and smaller system footprint, as objects that vary widely in specification can be sorted. In another example, more than one actuator may be used to sort the objects in multiple stages or steps. In a further example, more than one different sensor of a different type may be employed, for example, a magnetic sensor along with a light sensor, etc.

[0017] A first sensor or camera watches the object as it enters the system, for example by free falling from above the camera. The first sensor notes various information about the object, and then feeds that information to a controller, which actuates a sorting actuator to implement movement of the object so that it ends up sorted into a specific bin. Concurrent with the object falling and being sorted, one or more

additional sensors carefully watch the sorting process to judge how effective the sorting process was for the particular object. Based on scoring the efficacy of the sorting, the system engages a feedback loop or learning process to fine-tune the sorting rules and parameters so that subsequently sorted objects are more precisely separated by type.

[0018] Generally stated, described herein, in one aspect, is a system for sorting glass objects. For instance, the system includes a first sensor, a sorting actuator, a second sensor and a controller. The first sensor may be for observing the objects including colors. The sorting actuator may be for sorting the objects based on the colors. The second sensor may be for observing the sorted objects. The sorting actuator may be actuated by the controller using sorting rules, historical system data and observations of the objects, including the colors of the objects. Sorting scores may be calculated by the controller based on the observations of the sorted objects. The sorting rules may be updated by the controller using the sorting scores.

[0019] In another aspect, a system is provided. For instance, the system includes a first sensor, a sorting actuator, a second sensor and a controller. The first sensor may be for observing the objects. The sorting actuator may be for sorting the objects. The second sensor may be for observing the sorted objects. The sorting actuator may be actuated by the controller using sorting rules, historical system data and observations of the objects. The sorting rules may be updated by the controller using the observations of the sorted objects.

[0020] In one embodiment, the objects may include selected objects having predetermined colors and the system may learn the sorting rules by sorting the selected objects with the predetermined colors. In another embodiment, updating the sorting rules may include incrementally changing the sorting rules to improve the scoring of the sorting. In a further embodiment, the controller may be configured to save or load the sorting rules.

[0021] In one implementation, the system may include a free-fall section to allow the objects to fall past the sorting actuator. In another implementation, the system may include at least one colored background to facilitate sorting by color. In other examples, the first sensor and the second sensor may be the same or different sensors. And, in yet another example, the system may include a third sensor (or more sensors) for observing the sorting of the objects by the sorting actuator.

[0022] In a further aspect, a method is provided. Objects are observed, e.g., during free fall or traversal of a conveyor belt. The objects are sorted using sorting rules, historical system data and observations of the objects. The objects are observed. The sorting rules are updated using observations of the sorted objects. In one example, the method includes scoring the sorting and incrementally changing the sorting parameters to improve the scoring of the sorting. In another example, the method includes saving or loading the sorting rules. In a further example, the method includes sorting the objects by color. In such a case, the method may include using at least one colored background to facilitate sorting by color.

[0023] FIG. 1 depicts a system 100 for sorting an object 101, which is represented in multiple positions 101a-101c in the drawings. For instance, in the embodiment of FIG. 1, the system 100 includes a first sensor 110a, a second sensor 110b, and an optional third sensor 110c. The system 100 also

includes a controller 105 and at least one sorting actuator 120 (depending on the application, multiple stage sorting actuation may be employed). The sensors 110a-110c send sensor data to the controller 105, and the sorting actuator 120 is controlled by the controller 105 using a combination of sorting rules and sensor data.

[0024] In addition, light sources 115a, 115b may be used in conjunction with the respective sensors 110a, 110b to facilitate detection of colors of the objects 101. In conjunction with the light sources 115a, 115b, backgrounds 130a, 130b, having varying colors, may be used to effectuate the color detection. For example, color detection may use the reflection properties of colored material. If trying to remove red material, and using red light, green and blue material may show as very dark (close to black). The detection algorithm can then efficiently remove dark objects and sense only red objects. Similarly, since glass refracts, using a blue background and ambient white light, red glass may be detected by camera as black (very dark).

[0025] By way of overview, in one example, the object 101 free falls through the system 100, and first passes, at position 101a, by the first sensor 110a. The first sensor 110a feeds sensor data to the controller 105, which may use the sensor data to determine various characteristics of the object 101. Based on the sensor data and currently operable sorting rules, the controller 105 may actuate the sorting actuator 120 when the object 101 passes through position 101c. The sorting rules may include fixed sorting parameters as well as variable rules that are learned over the course of time by the system 100. Further details, including mathematical details of the sorting rules are set forth below with respect to FIG. 2.

[0026] In different embodiments, and depending on the application, the sorting actuator 120 may be a solenoid type, servo type, water valve type, or air type. Examples of the foregoing are as follows: a linear motion solenoid available from Shenzhen Zonhen Electric Appliances Co., of China; a PowerHD servo available from HuiDa RC International Inc., of China; a solenoid water valve available from Sizto Tech Corporation of Palo Alto, Calif.; or an MHJ solenoid air valve available from Festo AG of Esslingen am Neckar, Germany.

[0027] In one example, the sensors 110a-110c may be cameras, such as color cameras, infrared sensors, ultraviolet sensors, X-ray sensors, laser sensors or light data and ranging sensors, or combinations thereof. Such sensors are available from vendors such as Logitech, of Newark, Calif. or Kayeton Technology Company of Shenzhen, China. In another example, the sensors 110a-110c may be infrared or ultraviolet cameras, such as those available from Fuji of Tokyo, Japan. In further examples, X-Ray or Light Data and Ranging (LIDAR) sensors may be used for sensors 110a-110c. The controller 105 may be or include multiple components, such as processors or graphics processors available from Intel or Nvidia, both of Santa Clara, Calif.

[0028] FIG. 2 is a flowchart depicting a method 200 for sorting objects. The method 200 can be implemented by one or more programs running on the system 100, in particular running on the controller 105. Further details of the computing, storage, and related functions of the system 100, for enabling operation of the method 200, is set forth below with respect to FIG. 3.

[0029] In the embodiment of FIG. 2, the method 200 at block 202 starts, for example, in response to auto-detecting a flow of objects into the system 100 (FIG. 1) for sorting.

[0030] The concept of historical system data is now introduced. At any given point in time, the aggregate of all system data, such as prior sorting actions, prior object observations, etc., may be termed the historical system data. Of course, as time progresses, the historical system data continues to grow based upon new sorting actions and new observations of the objects, using one or more sensors such as cameras. In one example, the concept of pre-sort system state may more precisely be defined as including all relevant historical system data that is known at a given point in time right before a sorting action takes place. In such a case, the concept of post-sort system data may more precisely be defined as including all historical system data this is known at the point in time right after a sorting event takes place, e.g., after sorting actuation, the observation from sensors and the action are added to the history and become new state of the system. Generally speaking, the historical system data makes up the state of the system. A controller of the system may maintain a policy matrix that includes each known state, each action, and each average reward (e.g., represented by a score) expected when moving from a known state using a known action. This policy matrix or state table informs controller what is the best action to take given the current state. Initially, while the controller is still building this matrix or table, the controller may be configured to make a percentage of random action to learn which actions might be more advantageous. Also, as environment parameters change, for example the actuator slows, the reward will start showing negative values, resulting in the controller re-evaluating and updating the best action for a given state. After a few minutes of runtime, controller will refresh the policy matrix, and system will start performing the sorting as expected. Advantageously, this configuration allows the system to adapt as per changing conditions, because the system continues to modify its behavior based on the learning techniques disclosed herein, rather than adopting a fixed behavior.

[0031] Initially, the method 200 at block 204 observes the objects. By way of example, observations may include size, shape, color, opacity, material composition, moisture, temperature, or any other physical characteristic of the objects. In addition, observations may include velocity, acceleration, position (e.g., in three-dimensions), or any other kinetic information related to the objects. Further, the observations may include electrical data, magnetism data, chemical composition, vibration, sound, or any other such data related to the objects or the environment (e.g. ambient lighting conditions, wind speed and direction, temperature, etc.). In one example, the observations are fed to the controller 105 (FIG. 1), where it may be used and stored for later use.

[0032] Note that different sensors may be needed for different environments. For instance, acoustic, chemical, electrical, magnetic, radio, environmental, weather, moisture, humidity, flow, fluid velocity, radiation, particle, navigation, optical, pressure, displacement, acceleration, gyroscopic, force, density, proximity, and other sensors may be used to distinguish different objects, either alone or in combination.

[0033] Continuing, the method 200 at block 206 sorts the objects using sorting rules, historical system data and observations of the objects. For instance, the controller 105 may

use the observations, along with the sorting rules, including various parameters of the sorting rules, to determine how to sort the specific object. This may then be translated into a specific actuator instruction, so that the actuator causes the object to move by specified amount so that it falls into an appropriate sorting bin.

[0034] In one embodiment, the method 200 loads the sorting rules described above from a storage device. The stored sorting rules may have been learned over the course of time during other sorting runs, or may have been determined by an expert operator designing the specific parameters to be used in a specific sort, or some combination thereof. For instance, a thumb drive storage device including the sorting rules may be plugged into the system so that the system operates and behaves in a particular manner for a particular application. In one case, such pre-loaded configuration files, including details of the sorting rules, may be developed for use in glass sorting, metal sorting, plastic sorting, produce sorting, mail sorting, or any other sorting application.

[0035] After or during sorting, the method 200 at block 208 observes the objects. Observations of the objects after the sorting are then included in the aggregate known system data at a given point in time.

[0036] For example, the same parameters that were observed before sorting may now be measured after sorting, including physical, kinetic, chemical, or other data of the sorted object. The method 200 may observe the sorting process itself, e.g., by observing the sorting actuator activate and effectuate a movement of the object from its initial position. Alternately or additionally, the method 200 may observe the object after the sorting actuator has already performed its function, and provide a final state data observation of the object. And, the method and system advantageously allows for more sensor readings to take place, so that a third, fourth, or more sensors may provide data of the object. In some examples, a single sensor may track the object through the multiple stages, and observation data before, during and after sorting action (or actuation). In other applications, multiple discrete sensors may be deployed for convenience or simplicity. In some embodiments, the first sensor may be of one type, e.g., a camera, and the second sensor may be of a different type, e.g., a laser or a LIDAR sensor.

[0037] Next, the method 200 at block 210 updates the sorting rules using the observation data of the objects. In one example, updating the sorting rules may include defining a score function, and scoring the sorting on an object-by-object basis. The sorting rules may be incrementally changed after each object has been sorted, so that subsequent objects are sorted by sorting rules that have learned from the prior sorting operations.

[0038] After sorting numerous objects, the sorting rules currently in force may be saved to the system so that the learning can be reused when next sorting similar objects under similar conditions. Advantageously, sorting rules, once loaded, can then continue to benefit from the learning system and feedback afforded by the second (or more) sensors used by the method.

[0039] Finally, the method 200 at block 212 ends, when a batch of objects has been sorted. In one example, the method 200 may be run through batches of test items of known variation, which could be used to train the system to learn how to sort particular items. For instance, a first, preselected,

batch of objects (e.g., a bucket full) having varying sizes and varying shades of green may be fed into the system, and the system may be operated in a learning mode in which the system observes all the objects and learns that they are to be considered green objects. Similar training could be done to teach the system about brown glass and clear flint glass. Then, once the system learns about these objects, the system can be used to sort an entire truck load of recycling glass into different bins for green, brown, and clear flint glass.

[0040] Because such training could be done under real world conditions, variations in the drop height of the free-fall, average glass size in the batches, etc., can be automatically adjusted for by the system due to being trained by relatively small batches of glass. Of course, to the extent that conditions continue to repeat, the learning from the training, and the actual sorting results, can be saved as described above, and a library of sorting rules may be created for use in different environments.

[0041] In addition to object sorting system, other applications of the techniques disclosed herein include upgrades to existing sorting machines to improve their performance and/or provide flexibility to use operating condition or material outside the specifications of the current system. Further, another application is for an intelligent irrigation system, that constantly monitors, using one or more sensors, such as soil, temperature, pH level, plant/tree health/growth sensors, and uses actuators to release needed ingredients (e.g., water/fertilizer) at an individual plant/tree basis at a large scale. For example, the system can learn about local grub infestations and handle it without any manual or rule based intervention. In such a case, the concepts have been expanded beyond sorting and actuation of sorting to include a control system that includes observation with sensors, actuation of any process, and scoring functions.

[0042] In one example, Q-learning, which is a model free reinforcement learning technique, is used by the system. In one example, the State-action-reward-state-action (SARSA) algorithm for learning a Markov decision process policy, is used by the system. A person having ordinary skill in the art will understand the details of using Q-learning or SARSA, to take the historical data at a given time (t-x) and use it to determine an action at time (t).

[0043] Next, working examples of mathematical algorithms that may be employed in different embodiments of the system or method are set forth below.

[0044] In one example that does not use a feedback loop, $A_t = f(C_{t-x}(S_{t-x-y}))$, where:

A_t are action(s) taken at time t;

f is a function that determines the action(s) to take;

C_t is a function that determines the categories of objects found;

S_t represents all accumulated sensor inputs at time t;

x is the time delay between categorization being complete and the action being taken; and

y is the time delay between the sensor output being available and the categorization being complete.

[0045] In one example of the techniques disclosed herein, $A'_t = f(C'_{t-x}(S'_{t-x-y}), C'_t(S'_t), A'_t, R'_t(S'_t))$, where:

A'_t are action(s) taken at time t;

f is a function that determines the action(s) to take;

C'_t is a function that determines the categories of objects found;

S'_t represents all accumulated sensor inputs at time t; and

R'_t represents the results of the previous action.

[0046] For instance, f may be periodically changed to maximize the total overall result R' on an ongoing basis, so as to learn to sort better.

[0047] In one example, given the continual changes in sorting objective, lighting condition, input material, speed and other environmental factors, continually changing the function that determines the action to take has significant advantages over using a fixed action function.

[0048] By way of further explanation, a model-free reinforcement learning technique such as Q-learning may be employed as the above stated algorithm. Specifically, Q-learning may find an optimal action-selection policy for any given decision process. An action-value function may be learned that provides the expected utility of taking a given action in a given state, and thereafter the optimal policy may be followed. Such a policy may be rule-based, in that the agent selects actions based on the current state. After learning an action-value function, the optimal policy may be based on selecting the action with the highest value in each state. Advantageously, the present technique allows comparison of the expected utility of the available actions without requiring a precise mathematical model of the environment. In other words, through the selection of the reward function, informed by the multiple camera views and data, the system is invariant to the specific details of flow rate, separation of objects, etc., because it is always learning by experience rather than through an initial model. This allows as a further advantage the handling of stochastic transitions and rewards, leading to an optimal policy through the trial and error technique.

[0049] FIG. 3 depicts further details of the controller 105 (FIG. 1). In the embodiment of FIG. 3, the controller 105 includes an action agent 300 and a learning agent 310. The action agent 300 may be used to actuate the sorting actuator 120 (FIG. 1). The action agent 300 may include a memory 302, statistical agent policy parameters 304 and a processor 306. The memory 302 may be used to store the current and historical object data, input and output data, action history, etc. The parameters 304 may include the sorting rules, parameters, etc. The processor 306 may be used to compute the algorithms described above to implement the sorting rules, applying the loaded sorting rules or policies to the current state (e.g., the current object to be sorted).

[0050] In addition, the learning agent 310 may include both the learning functions and context, as well as the ability to store and load the sorting rules. For example, the learning agent 310 may include a memory 312, an optional policy interface 314, a processor 316 and a statistical policy/history controller 318. The memory 312 may include a larger store of historical data related to sorting of objects, similar to the memory 302 of the action agent 300. The policy interface 314 may include a variety of functions, including the ability to reset the system to the last known good state, begin learning, or save or load the sorting rules including sorting parameters. The processor 316 may include the ability to find statistical patterns in the sorting history in order to set the best parameters for choosing actions that result in correct sorting of the objects.

[0051] FIG. 4 depicts an example of operation of the system 100 of FIG. 1. The system 100 at step 402 performs actions and gets input from both a first and second sensor. Next, the system 100 at step 404 categorizes the observation data of the object from both of the sensors, including information obtained before and after sorting. Next, the

system **100** at step **406** stores the last action, input data, and reward data in memory. Next, the system **100** at step **408** sends the last N (e.g., **10**) input data, actions and rewards to the controller for processing. Next, the system **100** at step **410** decides programmatically on the next action. Finally, the system **100** at step **412** waits for the time interval or tick (e.g., 100 milliseconds) to pass, and returns to the start **401**. As may also be seen, the system **100** at step **420** passes new observations to the algorithms. Next, the system **100** at step **422** adjusts the policy, including the sorting rules. Finally, the system **100** at step **424** informs the controller of the new sorting rules and policies.

[0052] In another aspect, the system may be trained in order to perform a specific application. One specific training sequence is as follows:

[0053] First, start with a small amount (e.g., 100 pounds) of green glass that is broken and in various sizes, as would be found in the final mixture to be sorted. Next, pass the green glass through the system, operating in a command mode of “learn color that is the objective to be sorted” specifying that green glass is to be identified and classified.

[0054] As the green glass passes through the system, the system may find the characteristics of the input color using color histogram to find HSV (hue-saturation-value) or RGB (red-green-blue) color boundaries. In a variation, size and color could be determined as the objective.

[0055] Next, 100 pounds of other material, except green glass, that will be found in the final mixture to be sorted, may be passed through the system, operating in a command mode of “learn the color that is not the objective to be sorted.” Again, the system can then find the characteristics of the input color using color histogram to find HSV or RGB color boundaries to ignore or reject. And, similarly, in a variation, size and color could also be varied.

[0056] Next, the mixed material may be filled in the hopper and the feeder may be started to start the mixed glass flow through the system. The system may be commanded to start the first input and second reward sensors or cameras, as well as the actuator. A user of the machine may observe periodically to see if the machine has learned, by monitoring the output bins.

[0057] After such a trial run sequence has been performed, and has yielded material in good, sorted order, the full configuration may be saved by the system, for example to a non-volatile memory storage device such as a thumb drive. Now, the system may run as a normal, steady state operational system.

[0058] Alternatively, subsequently the system may be transported and set up in a different location, and may be initialized using the saved configuration, e.g., by inserting the thumb drive and loading the preconfigured settings which include the historical data. Next, the hopper may be filled and the feeder, sensors, actuators, etc., may be started to sort the items.

[0059] In another example, during steady state operation, troubleshooting steps may be used to automatically correct misfiring that is detected by the sensors (or by an operator). In such a case, if the misfiring takes place for greater than a predetermined time period, a bump command may be initiated, that can increase the propensity of the system to make adjustment to the current configuration and bring it to optimized state faster. If the bump command does not restore

the system to an operational steady state within a specified time frame, then the system may automatically or manually be restarted.

[0060] Aspects of the system and method for sorting objects, as described above, offer numerous advantages. For instance, the use of two or more sensors, which may be cameras, improves the technology of sorting by facilitating learning from experience. The use of multiple sensors of different types may also be used, for example by combining camera sensors with magnetic sensors. In such a manner. Also, sensors with different testing times may be used. For example, during the sorting process, there may be a sensor that is quick to give data on a specific object, but the post-sorting sensor may act in a more bulk manner to give an indication of the overall efficiency of the sorting. Because the system can be trained by feeding it material of different types (which it can then learn to differentiate), numerous other applications, beyond sorting recycling or goods are available. For instance, mail sorting, luggage handling at airports, factory assembly line monitoring, and other like applications can benefit from an overall system that uses multiple sensors and includes a learning algorithm as described herein.

[0061] To the extent that the claims recite the phrase “at least one of” in reference to a plurality of elements, this is intended to mean at least one or more of the listed elements, and is not limited to at least one of each element. For example, “at least one of an element A, element B, and element C,” is intended to indicate element A alone, or element B alone, or element C alone, or any combination thereof “At least one of element A, element B, and element C” is not intended to be limited to at least one of an element A, at least one of an element B, and at least one of an element C.

[0062] This written description uses examples to disclose the invention, including the best mode, and also to enable any person skilled in the art to practice the invention, including making and using any devices or systems and performing any incorporated methods. The patentable scope of the invention is defined by the claims, and may include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if they have structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal language of the claims.

[0063] In view of the foregoing, embodiments of the invention sort objects, such as glass objects. A technical effect is to enable the separation of mixed items so that they can be separately processed. As will be appreciated by one skilled in the art, aspects of the present invention may be embodied as a system, method, or computer program product. Accordingly, aspects of the present invention may take the form of an entirely hardware embodiment, an entirely software embodiment (including firmware, resident software, micro-code, etc.), or an embodiment combining software and hardware aspects that may all generally be referred to herein as a “service,” “circuit,” “circuitry,” “module,” and/or “system.” Furthermore, aspects of the present invention may take the form of a computer program product embodied in one or more computer readable medium(s) having computer readable program code embodied thereon.

[0064] Any combination of one or more computer readable medium(s) may be utilized. The computer readable

medium may be a computer readable signal medium or a computer readable storage medium. A computer readable storage medium may be, for example, but not limited to, an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, apparatus, or device, or any suitable combination of the foregoing. More specific examples (a non-exhaustive list) of the computer readable storage medium would include the following: an electrical connection having one or more wires, a portable computer diskette, a hard disk, a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM or Flash memory), an optical fiber, a portable compact disc read-only memory (CD-ROM), an optical storage device, a magnetic storage device, or any suitable combination of the foregoing. In the context of this document, a computer readable storage medium may be any tangible medium that can contain, or store a program for use by or in connection with an instruction execution system, apparatus, or device.

[0065] Program code and/or executable instructions embodied on a computer readable medium may be transmitted using any appropriate medium, including but not limited to wireless, wireline, optical fiber cable, RF, etc., or any suitable combination of the foregoing.

[0066] Computer program code for carrying out operations for aspects of the present invention may be written in any combination of one or more programming languages, including an object oriented programming language such as Java, Smalltalk, C++ or the like and conventional procedural programming languages, such as the “C” programming language or similar programming languages. The program code may execute entirely on the user’s computer (device), partly on the user’s computer, as a stand-alone software package, partly on the user’s computer and partly on a remote computer or entirely on the remote computer or server. In the latter scenario, the remote computer may be connected to the user’s computer through any type of network, including a local area network (LAN) or a wide area network (WAN), or the connection may be made to an external computer (for example, through the Internet using an Internet Service Provider).

[0067] Aspects of the present invention are described herein with reference to flowchart illustrations and/or block diagrams of methods, apparatus (systems) and computer program products according to embodiments of the invention. It will be understood that each block of the flowchart illustrations and/or block diagrams, and combinations of blocks in the flowchart illustrations and/or block diagrams, can be implemented by computer program instructions. These computer program instructions may be provided to a processor of a general purpose computer, special purpose computer, or other programmable data processing apparatus to produce a machine, such that the instructions, which execute via the processor of the computer or other programmable data processing apparatus, create means for implementing the functions/acts specified in the flowchart and/or block diagram block or blocks.

[0068] These computer program instructions may also be stored in a computer readable medium that can direct a computer, other programmable data processing apparatus, or other devices to function in a particular manner, such that the instructions stored in the computer readable medium produce an article of manufacture including instructions which

implement the function/act specified in the flowchart and/or block diagram block or blocks.

[0069] The computer program instructions may also be loaded onto a computer, other programmable data processing apparatus, or other devices to cause a series of operational steps to be performed on the computer, other programmable apparatus or other devices to produce a computer implemented process such that the instructions which execute on the computer or other programmable apparatus provide processes for implementing the functions/acts specified in the flowchart and/or block diagram block or blocks.

1. A system for sorting glass objects having different colors, the system comprising

a first sensor for observing the objects, including observing first observed colors of the objects;

a sorting actuator for sorting the objects based on the first observed colors of the objects;

a second sensor for observing second observed colors of the sorted objects after the sorting by the sorting actuator; and

a controller configured to

actuate the sorting actuator to perform a specific action to sort a specific object of the glass objects using sorting rules, the sorting rules being based on historical system data including observed colors from the first sensor and the second sensor of previously sorted objects of the glass objects, and a first observed color of the specific object of the glass objects,

calculate, after the sorting of the specific object by the sorting actuator, a sorting score based on a second observed color of the specific sorted object of the glass objects, and

update the sorting rules to create updated sorting rules, using the sorting rules, the first observed color, the second observed color, the sorting score and the specific action performed to sort the specific object, wherein the updated sorting rules are used in sorting subsequent objects of the glass objects.

2. The system of claim 1, wherein the objects include selected objects having predetermined colors and the system learns the sorting rules by sorting the selected objects with the predetermined colors.

3. The system of claim 1, wherein updating the sorting rules comprises incrementally changing the sorting rules to improve the scoring of the sorting.

4. The system of claim 1, wherein the controller is configured to save or load the sorting rules.

5. The system of claim 1, further comprising a free-fall section to allow the objects to fall past the sorting actuator.

6. The system of claim 5, further comprising at least one colored background to facilitate sorting by color.

7. The system of claim 1, wherein the first sensor and the second sensor are cameras.

8. The system of claim 1, further comprising a third sensor for observing the sorting of the objects by the sorting actuator.

9. A system for sorting objects, the system comprising:

a first sensor for observing the objects;

a sorting actuator for sorting the objects by performing specific actions;

a second sensor for observing the sorted objects; and

a controller configured to
actuate the sorting actuator using sorting rules to sort a
specific object of the objects, historical system data
and observations of the objects, and
update the sorting rules to create updated sorting rules
using the sorting rules, the observations of previ-
ously sorted objects of the sorted objects and the
specific actions performed to sort the previously
sorted objects.

10. The system of claim **9**, wherein the objects include
selected objects having predetermined characteristics and
the system learns the sorting rules by sorting the selected
objects with the predetermined characteristics.

11. The system of claim **9**, wherein updating the sorting
rules comprises scoring the sorting and incrementally chang-
ing the sorting parameters to improve the scoring of the
sorting.

12. The system of claim **9**, wherein the controller is
configured to save or load the sorting parameters.

13. The system of claim **1**, further comprising a free-fall
section to allow the objects to fall past the sorting actuator.

14. The system of claim **1**, wherein the first sensor and the
second sensor are cameras.

15. The system of claim **1**, further comprising a third
sensor for observing the sorting of the objects by the sorting
actuator.

16. A method for sorting objects, the method comprising:
observing the objects;
sorting the objects using sorting rules, historical system
data and observations of the objects;
observing the sorted objects;
updating the sorting rules to create updated sorting rules
using the observations of the objects before and after
sorting and actions used to sort the objects.

17. The method of claim **16**, further comprising scoring
the sorting and incrementally changing the sorting param-
eters to improve the scoring of the sorting.

18. The method of claim **16**, further comprising saving or
loading the sorting rules.

19. The method of claim **16**, further comprising sorting
the objects by color.

20. The method of claim **16**, further comprising using at
least one colored background to facilitate sorting by color.

* * * * *